

Application Serial No: 10/644,549
In reply to Office Action of 06 April 2006

Attorney Docket No. 84454

AMENDMENTS TO THE CLAIMS

1. (previously presented) An optical fiber coupler for connecting a first fiber optic element to a second fiber optic element, the coupler comprising:

a first fiber optic element extending in a first direction whereby to position a free end of said first fiber optic element in a selected zone;

a second fiber optic element extending into the selected zone from a direction generally opposite to the first direction to position a free end of said second fiber optic element in the selected zone and proximate the first fiber optic element free end; and

a cured optical grade epoxy resin body comprising the selected zone and enveloping the free ends of said fiber optic elements, wherein said body is provided with a cone-shaped end and a generally planar base end;

whereby to provide physical and optical connection between said first and second fiber optic elements.

Application Serial No: 10/644,549
In reply to Office Action of 06 April 2006

Attorney Docket No. 84454

2. (original) The coupler in accordance with claim 1 wherein said first fiber optic element comprises a single fiber optic strand and said second fiber optic element comprises a plurality of fiber optic strands.

3. (canceled)

4. (previously presented) The coupler in accordance with claim 1 wherein said first fiber optic element comprises a single fiber optic strand disposed in an apex of the cone-shaped end of said body and the single fiber optic strand extends through the apex and into said body.

5. (original) The coupler in accordance with claim 4 wherein said second fiber optic element comprises a plurality of fiber optic strands extending into said body through the base end.

6. (original) The coupler in accordance with claim 1 wherein said first and second fiber optic elements comprise at least one fiber optic strand and at least another fiber optic strand, respectively.

7. (original) The coupler in accordance with claim 6 wherein the free end of each of said at least one fiber optic strand of

Application Serial No: 10/644,549
In reply to Office Action of 06 April 2006

Attorney Docket No. 84454

said first fiber optic element and the free end of each of said at least another fiber optic strand of said second fiber optic element are butt-end terminated.

8. (original) The coupler in accordance with claim 1 wherein at least one of said first and second fiber optic elements comprises a plurality of fiber optic strands, the positions to which the free ends of said first and second elements extend being spaced apart by a distance allowing a sufficient extent of diffusion of light in the optical grade epoxy resin therebetween to couple light between each strand of one of said first and second fiber optic elements with each strand of the other of said elements.

9. (original) The coupler in accordance with claim 5 wherein said plurality of fiber optic strands is arranged in a ring-like pattern about a central axis of the cone-shaped end of said body.

10. (original) A method for connecting a first fiber optic element to a second fiber optic element, the method comprising the steps of:

Application Serial No: 10/644,549
In reply to Office Action of 06 April 2006

Attorney Docket No. 84454

providing a rigid elongated body having a cone-shaped end
and an opposite circular and planar base end;

coating outer surfaces of the body other than the base end
with a layer of mold making wax;

separating the body from the wax to provide a hollow wax
housing having a cone-shaped end and an open base end;

providing a hole in an apex of the housing cone-shaped end;

inserting a first fiber optic element comprising a single
fiber optic strand through the hole in a first
direction into the wax housing to position a free end
of the single fiber optic strand in the housing;

applying a sealant to the single strand at the housing apex
hole;

inserting the second fiber optic element comprising a
plurality of fiber optic strands into the wax housing
through the open-base end from a direction generally
opposite to the first direction to position free ends
of the plurality of fiber optic strands in the housing

Application Serial No: 10/644,549
In reply to Office Action of 06 April 2006

Attorney Docket No. 84454

and proximate the single fiber optic strand free end,
the positions to which the free ends of said first and
second element strands are inserted being spaced apart
by a distance to allow a sufficient extent of
diffusion of light in the optical grade epoxy resin
therebetween to couple light between the strand of the
first fiber optic element and each strand of the
second of the fiber optic elements;

filling the wax housing with optical grade epoxy resin and
permitting the resin to cure;

whereby to effect physical and optical connection between
the first and second fiber optic elements; and

removing the wax housing from the resin.

11. (previously presented) An optical fiber coupler for
connecting a first fiber optic element to a second fiber optic
element, the coupler comprising:

a first fiber optic element extending in a first direction
whereby to position a free end of said first fiber
optic element in a selected zone;

Application Serial No: 10/644,549
In reply to Office Action of 06 April 2006

Attorney Docket No. 84454

a second fiber optic element extending into the selected zone from a direction generally opposite to the first direction to position a free end of said second fiber optic element in the selected zone and proximate the first fiber optic element free end;

a cured optical grade epoxy resin body comprising the selected zone and enveloping the free ends of said fiber optic elements, wherein said body is provided with a cone-shaped end and a generally planar base end, whereby to provide physical and optical connection between said first and second fiber optic elements; and

wherein said first fiber optic element comprises a single fiber optic strand having a jacket surrounding a central region, said single fiber optic strand disposed in an apex of the cone-shaped end of said body and the single fiber optic strand extends through the apex and into said body;

Application Serial No: 10/644,549
In reply to Office Action of 06 April 2006

Attorney Docket No. 84454

wherein said second fiber optic element comprises a plurality of fiber optic strands extending into said body through the base end; and

wherein said plurality of fiber optic strands is arranged in a ring-like pattern about a central axis of the cone-shaped end of said body.

12. (currently amended) The coupler in accordance with claim [[13]] 11 wherein the free end of each of said at least one fiber optic strand of said first fiber optic element and the free end of each of said at least another fiber optic strand of said second fiber optic element are butt-end terminated.

13. (previously presented) The coupler in accordance with claim 11 wherein at least one of said first and second fiber optic elements comprises a plurality of fiber optic strands, the positions to which the free ends of said first and second elements extend being spaced apart by a distance allowing a sufficient extent of diffusion of light in the optical grade epoxy resin there between to couple light between each strand of one of said first and second fiber optic elements with each strand of the other of said elements.

Application Serial No: 10/644,549
In reply to Office Action of 06 April 2006

Attorney Docket No. 84454

14. (previously presented) The coupler in accordance with claim 11 wherein a length of the jacket covering the central region of the first fiber optic strand is removed to expose the central region of the first fiber optic strand to the optical grade epoxy resin body.